

## Hydro-Chem™ “PKW™” Wheeled Handline Extinguishing System

### Description:

Hydro-Chem™ “PKW™” Wheeled Handline Extinguishing System incorporates 300 lbs. of specialized “PKW™” dry chemical in trans- portable storage; a dual flow (HCHG) Series Hydro-Chem™ Handline Nozzle; and “flat lay” dry chemical delivery hose. This assembly, when combined with foam solution, is complete and ready to use in combating three dimensional and/or pressurized fuel fires. Unit provides dry chemical flows at 10 lbs/s and foam solution rates at 60, 95 or 125 gpm.

“PKW™” is a highly specialized siliconized Purple-K that is one of the most effective dry chemicals used to extinguish flammable and/or combustible liquid fires. Its distinctively deep purple color provides the fire fighter with the ability to stay ON-TARGET when it is project- ed to the fire within the foam/ water stream. This results in a quicker, more effective “knock-down,” and extinguishment.

### System includes:

Ansul wheeled fire extinguisher; flat lay discharge hose; 1.5” x 100 ft. coupled, 1.5” NH; Williams “PKW™” dry chemical 300 lbs.; HCHG, Series “Handgun” Hydro-Chem™ Nozzle.v



PKW™ Wheeled Extinguisher System	PKW™-WW-350 HCHG-60	PKW™-WW-350 HCHG-95	PKW™-WW-350 HCHG-125
Dry Chemical Capacity	300 lbs.	300 lbs.	300 lbs.
Dry Chemical Type	“PKW™” Purple K	“PKW™” Purple K	“PKW™” Purple K
Foam Solution Flow Range Flow (@ 100 psi)	60 gpm	95 gpm	125 gpm
Dry Chemical Flow (lbs/s)	10	10	10
Application	Class “B” Flowing Liquid Fires		